



# PRODUCT DATA SHEET

## Enviro Floors ENVIRO-DECK

---

### DESCRIPTION:

Enviro-Deck is an Environmentally timber coating or finishes to be used on exterior timber surfaces for domestic, commercial area's. Our special water-based/oil formulation with unique enviroshield technology will withstand all weather conditions giving complete protection.

Enviro-Deck is remarkably durable, long lasting semi transparent finish, a coating that enhances the features of the timber grain and weathers naturally, without danger of cracking, blistering and peeling. Very low odour and fast drying.

---

### WHERE TO USE:

For timber Substrates Only" Recommended for properly prepared new to slightly weathered, unsealed exterior timber surfaces such as Decks, Railings, garage doors, Shingles, timber Roofs, fences, Outdoor Timber Furniture, Walkways, Swimming Pool Decks, Pontoons, and Jetty or Jetties.

Around pools, ramps, stairs and all wet areas you should mix Enviro-Grip into Enviro-Deck.

Must Prep Before Applying Enviro-Deck Coating or Finish.

Coats Required: 3 Coats Required.

Spread Rate: 10-14 square metres per litre & this may vary.

Water Clean-Up

---

### DIRECTIONS FOR USE:

All paints and coatings that are on the timber surface must be thoroughly sanded back to bare timber. When coating new timber you will have to use Deck-Restorer before applying Enviro-Deck because of mill glaze & for old timber that has freshly been sanded you need to use Deck-Restorer before applying Enviro-Deck so the timber can accept the coatings into its pores of. Rinse thoroughly and allow to dry before coating. Lightly sand to remove remaining timber fibers/fuzz.

WARNING: Sanding or scraping timber is hazardous; wear eye protection, protective clothing, and gloves.

When spraying wears a respirator.

APPLICATION: Must apply between 5-32°C. Do not use if rain is expected within 4 hours. The timber surface must be completely dry.

DO NOT THIN DOWN ENVIRO-DECK PRODUCT.

Stir product occasionally throughout application. Test product for penetration and colour on a small hidden area before proceeding.

Use a nylon/polyester brush for more accuracy like around the edges & a lamb'swool applicator for the large area's. Work in small sections lightly saturating the surface

and immediately back-brush or use pad applicator to eliminate puddling, remove excess and evenly distribute the Finish.

Apply product end-to-end or to board lengths to prevent lap marks. Maintain a wet edge when applying.

Over application of finish will lead to surface failure including peeling and cracking.

Avoid applying finish too heavily.

DRY TIME 4 hours before recoat. Allow 72 hours for full cure.

Re-Coach: Wash down with Enviro Floors Deck-Clean, leave to dry, lightly sand then sweep or

vacuum off the dust, apply Enviro-Deck to manufactures instructions.

Maintenance:

Conduct routine maintenance checks yearly.

When washing the deck use Enviro Floors Deck-Clean it helps to look after Enviro-Deck.

Re-coating when the timber changes colour or water repellence diminishes due to wear, weathering and before it goes back to bear timber.

Why decks need maintaining some of the reasons decks deteriorate:

Sun's ultra violet rays breaking down timber cells, especially on the surface. Constant water seeping into the timber causing it to expand then it dries out and cracks.

SPILLS AND DISPOSAL: Prevent run o- into drains and waterways, always refer to State Land Waste Management Authority or the Environmental Protection Agency.

FIRST AID: For advice, contact a Poison Information Centre 13 11 26. If swallowed do NOT induce vomiting. If in eyes, hold eyelids apart and flush the eye continuously with running water.

Continue flushing until advised to stop by the Poison Information Centre or a doctor, or for at least 15 minutes.

If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue washing with water until advised to stop by the Poison Information Centre or a doctor.

Risk phrases: R36/38 Irritating to eyes & skin. R31 Contact with acids liberates toxic gas Ensure adequate ventilation when using.

Safety phrases: S(1/2) Keep out of reach of children. S28 After contact with skin remove contaminated clothing, wash immediately with plenty of soap-suds.

S45 In case of an accident if you feel unwell, seek medical advice immediately show the label where possible Poisons Schedule: S5 Caution.

All information regarding Enviro Floors Deck-Restorer product is supplied in good faith, however, responsibility rests with the product user for the suitability of the product in a particular application due to factors outside of the control of Enviro Floors. Such as weather, surface contamination, the technique of use, compatibility with the previous coating on the door, etc.

Whenever in doubt contact our hot line. If swallowed seek medical advice. For more information please go to our website and download the SDS paperwork.

Contact Our Technical Centre on: Email: [info@envirofloors.com.au](mailto:info@envirofloors.com.au)

---

## CLEAN-UP

Simple clean up tools and containers with water.

SUPERIOR FLOOR COATINGS WHICH LOOK AFTER YOUR HEALTH & ENVIRONMENT

Ph: 07 3293 2020 or Visit our website on [envirofloors.com.au](http://envirofloors.com.au)

©2026 Enviro Floors, All Rights Reserved. Enviro Floors® & Enviro Deck® is a registered trademark of Enviro Floors Pty Ltd.

File Name: EF-Pds-ENVIRO FLOORS Enviro-Deck.doc.

Page 2 of 3



---

## PROPERTIES AND DATA

Packaging - 1 Litre recyclable plastic container  
5 Litre recyclable plastic container  
10 Litre recyclable plastic container

**For further information on Toxicology of Surface Coatings, please do not hesitate to contact:**

Manufactured By: Enviro Floors  
Australian Customers Ph: 07 3293 2020  
International Customers Ph: +617 3293 2020  
Email: [info@envirofloors.com.au](mailto:info@envirofloors.com.au)  
Web: [envirofloors.com.au](http://envirofloors.com.au)

**Sales Office**  
Email: [info@envirofloors.com.au](mailto:info@envirofloors.com.au)  
**Technical Centre** - [info@envirofloors.com.au](mailto:info@envirofloors.com.au)

SUPERIOR FLOOR COATINGS WHICH LOOK AFTER YOUR HEALTH & ENVIRONMENT

Ph: 07 3293 2020 or Visit our website on [envirofloors.com.au](http://envirofloors.com.au)

©2026 Enviro Floors, All Rights Reserved. Enviro Floors® & Enviro Deck® is a registered trademark of Enviro Floors Pty Ltd.

File Name: *EF-Pds-ENVIRO FLOORS Enviro-Deck.doc*

Page 3 of 3

